

Leica Viva GS10

GNSS TECHNOLOGY

Self-learning GNSS	Leica RTKplus SmartLink (worldwide correction service) SmartLink fill (worldwide correction service)	Adaptive on-the-fly satellite selection Remote precise point positioning (3 cm 2D) ¹ Initial convergence to full accuracy typically 18 min, Re-convergence < 1 min Bridging of RTK outages up to 10 min (3 cm 2D) ¹
Leica SmartCheck	Continuous check of RTK solution	Reliability 99.99%
Signal tracking		GPS (L1, L2, L2C, L5), Glonass (L1, L2, L2C, L3 ²), BeiDou (B1, B2, B3 ²), Galileo (E1, E5a, E5b, Alt-BOC, E6 ²), QZSS (L1, L2C, L5, L6 ²), NavIC L5 ³ , SBAS (WAAS, EGNOS, MSAS, GAGAN), L-band
Number of channels		555 (more signals, fast acquisition, high sensitivity)
GNSS antenna	Standard or Choke-ring	Leica AS10 / AS05 or Leica AR10 / AR20 / AR25

MEASUREMENT PERFORMANCE & ACCURACY¹

Time for initialisation		Typically 4 s
Real-time kinematic (Compliant to ISO17123-8 standard)	Single baseline Network RTK	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm
Post processing	Static (phase) with long observations Static and rapid static (phase)	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm
Code differential	DGPS / RTCM	Typically 25 cm

COMMUNICATIONS

Communication ports	Lemo Bluetooth®	1 x USB and 2 x RS232 serial and Power Bluetooth® v2.00 + EDR, class 2
Communication protocols	RTK data protocols NMEA output Network RTK	Leica, Leica 4G, CMR, CMR+, RTCM 2.2, 2.3, 3.0, 3.1, 3.2 MSM NMEA 0183 V 4.00 and Leica proprietary VRS, FKP, iMAX, MAC (RTCM SC 104)
External data links	Up to 3 simultaneously	GSM / GPRS / UMTS / CDMA / VHF / UHF (up to 28800 bps over air) modem Phone / Radio modem in Leica GFU housing (IP67)

GENERAL

Field controller and software	Leica Captivate software Leica SmartWorx Viva software	Leica CS20 field controller, Leica CS35 tablet Leica CS10 and CS15 field controller
User interface	Buttons and LEDs Web server	On / Off and Function button, 8 status LEDs Full status information and configuration options
Data recording	Storage Data type and recording rate	Removable SD card, 8 GB Leica GNSS raw data and RINEX data up to 20 Hz
Power management	Internal power supply External power supply Operation time ⁴	2 exchangeable Li-Ion batteries (6 Ah / 7.4 V) Nominal 12 V DC, range 10.5 - 28 V DC 15h receiving (Rx) data with UHF radio, 13 h transmitting data with UHF radio (1W), 14 h Rx / Tx data with phone modem
Weight and Dimensions	Weight Dimensions	1.20 kg (GS10) / 5.40 kg standard RTK rover setup using pole and backpack 212 mm x 166 mm x 79 mm
Environmental	Temperature Drop Proof against water, sand and dust Vibration Humidity Functional shock	-40 to 65°C operating, -40 to 80°C storage Withstands topple over from a 2m survey pole onto hard surfaces IP68 (IEC60529 / MIL STD 810G 506.5 I / MIL STD 810G 510.5 I / MIL STD 810G 512.5 I) Withstands strong vibration (ISO9022-36-08 / MIL STD 810G 514.6 Cat.24) 100% (ISO9022-13-06 / ISO9022-12-04 / MIL STD 810G 507.5 I) 40 g / 15 to 23 msec (MIL STD 810G 516.6 I)

LEICA VIVA GS10 - GNSS RECEIVER

SUPPORTED GNSS SYSTEMS

Multi-frequency	✓	✓
GPS / GLONASS / Galileo / BeiDou / QZSS	✓ / • / • / • / •	✓ / ✓ / ✓ / ✓ / ✓ / ✓

RTK PERFORMANCE

DGPS/RTCM. RTK Unlimited, Network RTK	✓	✓
SmartLink fill / SmartLink	• / •	✓ / •

POSITION UPDATE & DATA RECORDING

5 Hz / 20 Hz positioning	✓ / ✓	✓ / ✓
Raw data / RINEX data logging / NMEA out	✓ / • / •	✓ / ✓ / ✓

ADDITIONAL FEATURES

RTK reference station functionality	✓	✓
-------------------------------------	---	---

✓ Standard

• Optional