

Leica Viva GS15

GNSS TECHNOLOGY

Self-learning GNSS	Leica RTKplus SmartLink (worldwide correction service) SmartLink fill (worldwide correction service)	Adaptive on-the-fly satellite selection Remote precise point positioning (3 cm 2D) ¹ Initial convergence to full accuracy 20 - 40 min, Re-convergence < 1 min Bridging of RTK outages up to 10 min (3 cm 2D) ¹
Leica SmartCheck	Continuous check of RTK solution	Reliability 99.99%
Signal tracking		GPS (L1, L2, L2C, L5), Glonass (L1, L2), BeiDou (B1, B2, B3 ²), Galileo (E1, E5a, E5b, Alt-BOC, E6 ²), QZSS ³ , SBAS (WAAS, EGNOS, MSAS, GAGAN), L-band
Number of channels		555 (more signals, fast acquisition, high sensitivity)

MEASUREMENT PERFORMANCE & ACCURACY¹

Time for initialisation		Typically 4 s
Real-time kinematic (Compliant to ISO17123-8 standard)	Single baseline Network RTK	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm
Post processing	Static (phase) with long observations Static and rapid static (phase)	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm
Code differential	DGPS / RTCM	Typically 25 cm

COMMUNICATIONS

Communication ports	Lemo Bluetooth®	USB and RS232 serial Bluetooth® v2.00 + EDR, class 2
Communication protocols	RTK data protocols NMEA output Network RTK	Leica, Leica 4G, CMR, CMR+, RTCM 2.2, 2.3, 3.0, 3.1, 3.2 MSM NMEA 0183 V 4.00 and Leica proprietary VRS, FKP, iMAX, MAC (RTCM SC 104)
Built-in data links	3.5G phone modem Radio modem	Fully integrated, internal or external antenna Fully integrated, receive and transmit, internal or external antenna 403 - 470 MHz, 1 W output power, up to 28800 bps over air
External data links		GSM / GPRS / UMTS / CDMA and UHF / VHF modem

GENERAL

Field controller and software	Leica Captivate software Leica SmartWorx Viva software	Leica CS20 field controller, Leica CS35 tablet Leica CS10 and CS15 field controller
User interface	Buttons and LEDs Web server	On / Off and Function button, 8 status LEDs Full status information and configuration options
Data recording	Storage Data type and recording rate	Removable SD card, 8 GB Leica GNSS raw data and RINEX data up to 20 Hz
Power management	Internal power supply External power supply Operation time ⁴	2 exchangeable Li-Ion batteries (2.6 Ah / 7.4 V) Nominal 12 V DC, range 10.5 - 28 V DC 10 h receiving (Rx) data with internal radio, 9 h transmitting (Tx) data with internal radio, 7.5 h Rx / Tx data with internal phone modem
Weight and Dimensions	Weight Diameter x Height	1.34 kg (GS15) / 3.30 kg standard RTK rover setup on pole 196 mm x 198 mm
Environmental	Temperature Drop Proof against water, sand and dust Vibration Humidity Functional shock	-40 to 65°C operating, -40 to 80°C storage Withstands topple over from a 2m survey pole onto hard surfaces IP68 (IEC60529 / MIL STD 810G 506.5 I / MIL STD 810G 510.5 I / MIL STD 810G 512.5 I) Withstands strong vibration (ISO9022-36-08 / MIL STD 810G 514.6 Cat.24) 100% (ISO9022-13-06 / ISO9022-12-04 / MIL STD 810G 507.5 I) 40 g / 15 to 23 msec (MIL STD 810G 516.6 I)

LEICA VIVA GS15 - GNSS SMARTANTENNA	Basic	Performance	Unlimited
SUPPORTED GNSS SYSTEMS			
Multi-frequency	•	✓	✓
GPS / GLONASS / Galileo / BeiDou	✓ / • / • / •	✓ / • / • / •	✓ / ✓ / ✓ / ✓
RTK PERFORMANCE			
DGPS/RTCM, RTK Unlimited, Network RTK	•	✓	✓
SmartLink fill / SmartLink	• / •	• / •	✓ / •
POSITION UPDATE & DATA RECORDING			
5 Hz / 20 Hz positioning	✓ / •	✓ / ✓	✓ / ✓
Raw data / RINEX data logging / NMEA out	✓ / • / •	✓ / • / •	✓ / ✓ / ✓
ADDITIONAL FEATURES			
RTK reference station functionality	•	✓	✓

✓ Standard

• Optional