

Leica RTC360 Product Specifications

GENERAL

3D laser scanner	High-speed 3D laser scanner with integrated HDR spherical imaging system and Visual Inertial System (VIS) for real time registration
------------------	--

PERFORMANCE

Data acquisition	< 2 mins for complete full dome scan and spherical HDR image at 6mm @ 10 m resolution
Real time registration	Automatic point cloud alignment based on real time tracking of scanner movement between setups based on Visual Inertial System (VIS) by video-enhanced inertial measurement unit
Double scan	Automatic removal of moving objects

SCANNING

Distance measurement	High-speed, high dynamic time of flight enhanced by Waveform Digitising (WFD) technology
Laser class	1 (in accordance with IEC 60825-1:2014), 1550 nm (invisible)
Field of view	360° (horizontal) / 300° (vertical)
Range	Min. 0.5 - up to 130 m
Speed	Up to 2,000,000 pts / sec
Resolution	3 user selectable settings (3/6/12 mm @ 10 m)
Accuracy*	Angular accuracy 18" Range accuracy 1.0 mm + 10 ppm 3D point accuracy 1.9 mm @ 10 m 2.9 mm @ 20 m 5.3 mm @ 40 m
Range noise* **	0.4 mm @ 10 m, 0.5 mm @ 20 m

IMAGING

Camera	36 MP 3-camera system captures 432 MPx raw data for calibrated 360° x 300° spherical image
Speed	1 minute for full spherical HDR image at any light condition
HDR	Automatic, 5 brackets

NAVIGATION SENSORS

Visual Inertial System	Video enhanced inertial measuring system to track movement of the scanner position relative to the previous setup in real time
Tilt	IMU based, Accuracy: 3' for any tilt
Additional sensors	Altimeter, Compass, GNSS

OPERATION

On scanner	Touch-screen control with finger touch, full colour WVGA graphic display 480 x 800 pixels
Mobile devices	Leica Cyclone FIELD 360 app for iPad or Android tablets including: - Remote control of scan functions - 2D & 3D data viewing - Tagging - Automatic alignment of scans
Wireless	Integrated wireless LAN (802.11 b/g/n)
Data storage	Leica MS256, 256 GB exchangeable USB 3.0 flash drive

DESIGN & PHYSICAL

Housing	Aluminium frame and sidecovers
Dimensions	120 mm x 240 mm x 230 mm / 4.7" x 9.4" x 9.1"
Weight	5.35 kg / 11.7 lbs, nominal (without batteries)
Mounting mechanism	Quick mounting on 5/8" stub on lightweight tripod / optional tribrach adapter / survey tribrach adapter available

POWER

Internal battery	2 x Leica GEB361 internal, rechargeable Li-Ion batteries. Duration: Typically up to 4 hours Weight: 340 g per battery
External	Leica GEV282 AC adapter

ENVIRONMENTAL

Operating temperature	-5° to +40°C
Storage temperature	-40° to +70°C
Dust/Humidity***	Solid particle/liquid ingress protection IP54 (IEC 60529)