

Leica TS16 Total Station

ANGLE MEASUREMENT

Accuracy ¹ Hz and V	■ Absolute, continuous, diametrical	1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon)
--------------------------------	-------------------------------------	--

DISTANCE MEASUREMENT

Range ²	■ Prism (GPR1, GPH1P) ³ ■ Non-Prism / Any surface ^{4,9}	0.9 m to 3,500 m R500: 0.9 m to >500 m R1000: 0.9 m to >1,000 m
Accuracy / Measurement time	■ Single (prism) ^{2,5} ■ Single (prism fast) ^{2,5} ■ Single (any surface) ^{2,4,5,6}	1 mm + 1.5 ppm / typically 2.4 s 2 mm + 1.5 ppm / typically 1.5 s ¹¹ 2 mm + 2 ppm / typically 2 s ⁷
Laser dot size	At 50 m	8 mm x 20 mm
Measurement technology	System analyser	Coaxial, visible red laser

IMAGING

Overview camera	■ Sensor ■ Field of view ■ Frame rate	5 megapixel CMOS sensor 19.4° Up to 20 frames per second
-----------------	---	--

AUTOMATIC AIMING - ATRplus

Target aiming range ² / Target locking range ²	■ Circular prism (GPR1, GPH1P) ■ 360° prism (GRZ4, GRZ122)	■ 1,500 m / 1,000 m ■ 1,000 m / 1,000 m
Accuracy ^{1,2} / Measurement time	ATRplus angle accuracy Hz, V	1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon) / typically 3-4 s

LASER GUIDE

Spot Size ⁸ / Range	■ Daylight: 30 mm @250 m ■ Darkness: 65 mm @300 m	250 m 500 m
--------------------------------	--	----------------

POWERSEARCH

Range / Search time	360° prism (GRZ4, GRZ122)	300 m / typically 5 s
---------------------	---------------------------	-----------------------

GUIDE LIGHT (EGL)

Working range / Accuracy		5 - 150 m / typically 5 cm @ 100 m
--------------------------	--	------------------------------------

GENERAL

Operating System / Field Software	Windows EC7 / Leica Captivate with apps	
Processor	TI OMAP4430 1GHz Dual-core ARM® Cortex™- A9 MPCore™	
AutoHeight module for automatic instrument height measurement	■ Distance accuracy ■ Distance range	1.0 mm (1 Sigma) 0.7 m to 2.7 m
Display and keyboard	5" (inch), WVGA, colour, touch, face I standard / face II optional	37 keys, illumination
Power management	Exchangeable Lithium-Ion battery	Operating time up to 8 h
Data storage	Internal memory / Memory card	2 GB / SD card 1 GB or 8 GB
Interfaces	RS232, USB, Bluetooth®, WLAN	
Weight	Total station including battery	5.1 - 5.8 kg
Environmental specifications	■ Working temperature range ■ Dust & Water (IEC 60529) / Humidity	-20°C to +50°C IP55 / 95%, non-condensing

LEICA TS16 TOTAL STATIONS	TS16 M	TS16 A	TS16 G ¹⁰	TS16 P	TS16 I
Angular measurement	✓	✓	✓	✓	✓
Distance measurement to prism	✓	✓	✓	✓	✓
Distance measurement to any surface	✓	✓	✓	✓	✓
Automatic target aiming (ATRplus)	✗	✓	✓	✓	✓
Laser Guide	✗	✗	✓	✗	✗
PowerSearch (PS)	✗	✗	✗	✓	✓
Overview camera	✗	✗	✗	✗	✓
Guide Light (EGL)	✓	✓	✗	✓	✓